

20 PRO B-MODULE RIPPLE

8W RIPPLE EFFECT LED MODULE



AVAILABLE OPTIONS

LED MODULE LIGHT THEME

**Configurable by DALI or Wireless Configurator*

Ripple - 4 Modes



Ivory



Aqua




Golden



Sky Blue

BEAM ANGLE



CONTROL INTERFACE



DA



DMX




CSB

INPUT



24V

DIMENSIONS (MM)



LED Module

SPECIFICATIONS

Family Type	20 series LED modules and engines
Typical Operating Voltage	24V
Typical Operating Current	330mA
System / Input Power	8W
Beam Angles	55°
Weight	100g
Compatibility	Compatible with ELR size-2 fixtures
Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10
Light Theme	Ripple - Ivory, Aqua, Golden, Sky Blue
CRI	N/A
SDCM	N/A
Control Interface	DALI (NFC COPY & PASTE), DMX, CASAMBI

Configuration	Light theme, brightness and movement speed
Colour	Black
Materials	Aluminium, glass
Ingress Protection	IP54 (LED MODULE), IP40 (CONTROL BOARD)
Mains Voltage	24V DC constant voltage
Power Factor	N/A
Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability Mark	F
Safety Class	Class 3
Standards	IEC 62031
Regulatory Markings	CE, CB, CCC, RoHS

20 PRO B-MODULE RIPPLE

Height (m)		Emax (lx)	LED Module		Luminous Flux (lm)
		55°	Type	Input Power	Dapple
1	E(0°)	145	20 Pro Ripple	8W	55°
	Cone Ø (m)	1.39			
2	E(0°)	36			
	Cone Ø (m)	2.78			
3	E(0°)	16			
	Cone Ø (m)	4.17			
4	E(0°)	9			
	Cone Ø (m)	5.56			
5	E(0°)	6			
	Cone Ø (m)	6.95			

ORDERING MATRIX CHART

LED Module				Control			
Input Power		Beam Angle		Light Theme		Interface	
ELR20P-BM.8	8W	55	55°	R1-IV	Ripple - Ivory	DA	DALI
				R1-AQ	Ripple - Aqua	DMX	DMX
				R1-GD	Ripple - Golden	CSB	Casambi
				R1-SB	Ripple - Sky Blue		

Wireless configurator [BFN-RPWC] is sold separately.

example: ELR20P-BM.8.20.D4.DA