


35 PRO B-MODULE CROWN

8W CROWN EFFECT LED MODULE



AVAILABLE OPTIONS	
LED MODULE LIGHT THEME <i>*Configurable by DALI or Wireless Configurator</i>	Crown - 4 Modes  Cool Graphite Warm Graphite Golden Silver
BEAM ANGLE	 20° 35° 60°
CONTROL INTERFACE	 DA DMX CSB
INPUT	 24V
DIMENSIONS (MM)	
59 (60°) 73 (35°) 75 (20°)  Ø51	

LED Module

SPECIFICATIONS

Family Type	35 Series
Typical Operating Voltage	24V
Typical Operating Current	330mA
System / Input Power	8W
Colour	Black
Materials	Aluminium, plastic, glass
Compatibility	Compatible with ELR size-3 fixtures
Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10
Beam Angles	20°, 35°, 60°
Light Theme	CROWN - 4 modes: Cool Graphite, Warm Graphite, Golden, Silver
CRI	N/A
SDCM	N/A

Ingress Protection	IP54 (LED module only)
Weight	160g
Control Interface	Activator with DALI, DMX interface
Configuration	Light theme, brightness and movement are configurable via DALI, DMX, Casambi or wireless configurator
Mains Voltage	24V DC constant voltage
Power Factor	N/A
Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability Mark	F
Safety Class	Class 3
Standards	IEC 62031
Regulatory Markings	CE, RoHS

35 PRO B-MODULE CROWN

Height (m)		E _{max} (lx)			LED Module		Luminous Flux (lm)		
		20°	35°	60°	Type	Input Power	CROWN		
1	E(0°)	2383	2004	396	35 Pro CROWN	8W	20°	35°	60°
	Cone Ø (m)	0.47	0.68	1.43			280	350	610
2	E(0°)	596	501	99					
	Cone Ø (m)	0.94	1.36	2.86					
3	E(0°)	265	223	44					
	Cone Ø (m)	1.41	2.04	4.29					
4	E(0°)	149	125	25					
	Cone Ø (m)	1.88	2.72	5.72					
5	E(0°)	95	80	16					
	Cone Ø (m)	2.35	3.40	7.15					

ORDERING MATRIX CHART

LED Module						Control	
Input Power		Beam Angle		Light Theme		Interface	
ELR35P-BM.8	8W						
		20	20°	CR4	Crown - 4 Modes	DA	DALI
		35	35°	CR1GO	Crown - Golden	DMX	DMX
		60	60°	CR1SL	Crown - Silver	CSB	Casambi

Wireless configurator [BFN-DPWC] is sold separately.

example: ELR35P-BM.8.35.CR4.DA