

20 PLE B-MODULE DAPPLE

8W DAPPLE EFFECT LED ENGINE



AVAILABLE OPTIONS

LED MODULE LIGHT THEME

Dapple - 4 modes



Cool
Graphite



Warm
Graphite



Golden



Silver

**Configurable by DALI or
Wireless Configurator.*

BEAM ANGLE



CONTROL INTERFACE



(DA)



(DMX)



(CSB)



(DA Copy
& Paste)

INPUT



(24V)

DIMENSIONS (MM)



LED Module

SPECIFICATIONS

Family Type	20 series LED modules and engines	Ingress Protection	IP54 (LED MODULE), IP40 (CONTROL BOARD)
Typical Operating Voltage	24V	Mains Voltage	24V DC constant voltage
Typical Operating Current	330mA	Power Factor	N/A
System / Input Power	8W	Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Beam Angles	20°	Flammability Mark	F
Weight	100g	Safety Class	Class 3
Compatibility	Compatible with ELR size-2 fixtures	Standards	IEC 62031
Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10	Regulatory Markings	CE, CB, CCC, RoHS
Light Theme	Dapple - 4 modes: Cool Graphite, Warm Graphite, Golden, Silver		
CRI	N/A		
SDCM	N/A		
Control Interface	DALI (NFC COPY & PASTE), DMX, CASAMBI		
Configuration	Light theme, brightness and movement speed		
Colour	Black		
Materials	Aluminium, glass		

20 PLE B-MODULE DAPPLE

Height (m)		Emax (lx)	LED Module		Luminous Flux (lm)
		20°	Type	Input Power	Dapple
1	E(0°)	2383	20 PLE Dapple	8W	280
	Cone Ø (m)	0.47			
2	E(0°)	596			
	Cone Ø (m)	0.94			
3	E(0°)	265			
	Cone Ø (m)	1.41			
4	E(0°)	149			
	Cone Ø (m)	1.88			
5	E(0°)	95			
	Cone Ø (m)	2.35			

ORDERING MATRIX CHART

LED Module						Control	
Input Power		Beam Angle		Light Theme		Interface	
ELR20PLE-BM.8		8W	20°	D4	Dapple - 4 Modes	DA AN	DALI 0-10V*

*0-10V is valid for brightness control only. Light theme and movement have to be configured via wireless configurator. Wireless configurator is sold separately.

example: ELR20PLE-BM.8.20.D4.DA