

35 PRO B-MODULE DAPPLE

8W DAPPLE EFFECT LED MODULE



AVAILABLE OPTIONS

LED MODULE
LIGHT THEME

Dapple - 4 modes



Cool
Graphite



Warm
Graphite



Golden



Silver

**Configurable by DALI or
Wireless Configurator.*

BEAM ANGLE



CONTROL
INTERFACE




**0-10V is valid for brightness
control only. Light theme and
movement have to be
configured via wireless
configurator.*

INPUT



(24V)

DIMENSIONS (MM)



SPECIFICATIONS

Family Type	35 Series	Ingress Protection	IP54 (LED module only)
Typical Operating Voltage	24V	Weight	160g
Typical Operating Current	330mA	Control Interface	Activator with DALI interface
System / Input Power	8W	Configuration	Light theme, brightness and movement are configurable via DALI or wireless configurator
Colour	Black	Mains Voltage	24V DC constant voltage
Materials	Aluminium, plastic, glass	Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Compatibility	Compatible with ELR size-3 fixtures	Flammability Mark	F
Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10	Safety Class	Class 3
Beam Angles	20°, 35°, 60°	Standards	IEC 62031
Light Theme	Dapple - 4 modes: Cool Graphite, Warm Graphite, Golden, Silver	Regulatory Markings	CE, RoHS

35 PRO B-MODULE DAPPLE

Height (m)		E _{max} (lx)			LED Module		Luminous Flux (lm)		
		20°	35°	60°	Type	Input Power	Dapple		
1	E(0°)	2383	2004	396	35 Pro Dapple	8W	20°	35°	60°
	Cone Ø (m)	0.47	0.68	1.43			280	350	610
2	E(0°)	596	501	99					
	Cone Ø (m)	0.94	1.36	2.86					
3	E(0°)	265	223	44					
	Cone Ø (m)	1.41	2.04	4.29					
4	E(0°)	149	125	25					
	Cone Ø (m)	1.88	2.72	5.72					
5	E(0°)	95	80	16					
	Cone Ø (m)	2.35	3.40	7.15					

ORDERING MATRIX CHART

LED Module						Control	
Input Power		Beam Angle		Light Theme		Interface	
_____		_____		_____		_____	
ELR35P-BM.8	8W	20	20°	D4	Dapple - 4 Modes	DA	DALI
		35	35°			AN	0-10V*
		60	60°				

*0-10V is valid for brightness control only. Light theme and movement have to be configured via wireless configurator.
Wireless configurator is sold separately.

example: ELR35P-BM.8.35.D4.DA