

20 PRO B-MODULE RIPPLE


8W RIPPLE EFFECT LED MODULE



AVAILABLE OPTIONS

LED MODULE LIGHT THEME


Ripple - 3 modes



Ivory



Aqua



Golden

**Configurable by DALI or
Wireless Configurator.*

BEAM ANGLE



CONTROL INTERFACE



(DA)



(DMX)



(CSB)




(DA Copy
& Paste)

INPUT



(24V)

DIMENSIONS (MM)



LED Module

SPECIFICATIONS

Family Type	20 series LED modules and engines	Ingress Protection	IP54 (LED MODULE), IP40 (CONTROL BOARD)
Typical Operating Voltage	24V	Mains Voltage	24V DC constant voltage
Typical Operating Current	330mA	Power Factor	N/A
System / Input Power	8W	Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Beam Angles	20°	Flammability Mark	F
Weight	100g	Safety Class	Class 3
Compatibility	Compatible with ELR size-2 fixtures	Standards	IEC 62031
Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10	Regulatory Markings	CE, CB, CCC, RoHS
Light Theme	Ripple - Ivory, Aqua, Golden		
CRI	N/A		
SDCM	N/A		
Control Interface	DALI (NFC COPY & PASTE), DMX, CASAMBI		
Configuration	Light theme, brightness and movement speed		
Colour	Black		
Materials	Aluminium, glass		

20 PRO B-MODULE RIPPLE

Height (m)		Emax (lx)	LED Module		Luminous Flux (lm)
		55°	Type	Input Power	Dapple
1	E(0°)	145	20 Pro Ripple	8W	55°
	Cone Ø (m)	1.39			160
2	E(0°)	36			
	Cone Ø (m)	2.78			
3	E(0°)	16			
	Cone Ø (m)	4.17			
4	E(0°)	9			
	Cone Ø (m)	5.56			
5	E(0°)	6			
	Cone Ø (m)	6.95			

ORDERING MATRIX CHART

LED Module				Control	
Input Power	Beam Angle	Light Theme		Interface	
ELR20P-BM.8	8W	55°	R1-IV	DA	DALI
			R1-AQ	AN	0-10V*
			R1-GD		

*0-10V is valid for brightness control only. Light theme and movement have to be configured via wireless configurator. Wireless configurator is sold separately.

example: ELR20P-BM.8.20.D4.DA