

NEBULA 3 SURFACE

IP 66 IK08

DC CONSTANT VOLTAGE SURFACE MOUNTED LUMINAIRE




AVAILABLE OPTIONS				
FIXTURE COLOUR OPTIONS				
	Matt Grey	Matt Black	Brushed Bronze	Brushed Brass
ACCESSORIES				
	Shadow D1	Shadow D2	Shadow D3	
LED MODULE				
	50PLE-BM Dapple 	50PLE	20° 35° 55° 60°	✓ ✓ ✓ ✓
Ripple 	50PLE		✓	
CONTROL INTERFACE				
	DA	DMX	CSB	
INPUT				
	24V			




NEBULA 3 SURFACE

IP 66 IK08

DIMENSIONS (MM)



NEBULA 3 SURFACE 66 IK08



SPECIFICATIONS

FIXTURE	
Family Type	NEBULA
Fixture Colours	Matt Grey (RAL7001), matt black (RAL9011), brushed bronze, brushed brass, brushed copper
Materials	Aluminium, Marine Grade Coating, Sealed Hard Anodising
Accessories	Shadow enhancer
Ingress Protection	IP66, IK08
DC Input Cable	Supplied with 1m cable. Custom length available upon request

LED MODULE & DRIVER	
Family Type	35, 50 series LED module and engines
Typical Operating Voltage	24V
Typical Operating Current	330mA - 495mA
System / Input Power	8W, 12W

Beam Angles	Dapple 20°, 35°, 60° / Ripple 55°
Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10
Light Themes	Cool Graphite, Warm Graphite, Golden, Silver, Ivory, Aqua, Sky Blue
Control Interface	DALI (NFC Copy & Paste), DMX, CASAMBI
Mains Voltage	24V DC constant voltage
Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability Mark	F
Safety Class	Class 3
Standards	IEC 62031
Regulatory Markings	CE, RoHS

FIXTURE ORDERING MATRIX CHART

Type	Fixture					
	Ingress Protection		Colour	Cable Length		
NEBULA-3SM-B	IP66	IP66	GR	Matt Grey	1M	1000mm
			MB	Matt Black	3M	3000mm
			BBZ	Brushed Bronze	5M	5000mm
			BBR	Brushed Brass		
			BCP	Brushed Copper		

Type	Accessories		Fixture Size
	Accessory		
MPACC	SHA-D1	Shadow D1	-3
	SHA-D2	Shadow D2	
	SHA-D3	Shadow D3	

example: NEBULA-3SM-B.IP66.MB.1M

example: MPACC.SHA-D1-3

Note: Custom RAL colour options available.

LED MODULE & DRIVER ORDERING MATRIX CHART

LED Module				Control			
Input Power		Beam Angle		Light Theme		Interface	
ELR50PLE-BM.12	12W	20	20°	D4	Dapple - 4 Modes	DA	DALI
						DMX	DMX
						CSB	Casambi
ELR50PLE-BM.8	8W	35	35°				

example: ELR50PLE-BM.8.35.D4.DA

LED Module				Control			
Input Power		Beam Angle		Light Theme		Interface	
ELR50PLE-BM.12	12W	55	55°	R1-IV	Ripple - Ivory	DA	DALI
				R1-AQ	Ripple - Aqua	DMX	DMX
				R1-GD	Ripple - Golden	CSB	Casambi
				R1-SB	Ripple - Sky Blue		
ELR50PLE-BM.8	8W						

example: ELR50PLE-BM.8.55.R1-AQ.DA