

NEBULA 3 WALL MOUNT

IP 68 IK08

DC CONSTANT VOLTAGE WALL MOUNTED LUMINAIRE



#WALL MOUNT
#DOWN



#WALL MOUNT
#UP DOWN



AVAILABLE OPTIONS									
FIXTURE COLOUR OPTIONS									
	Matt Grey	Matt Black	Brushed Bronze	Brushed Brass	Brushed Copper				
ACCESSORIES									
	Shadow D1	Shadow D2	Shadow D3						
LED MODULE	 50PLE-BM								
	Dapple					50PLE	✓	✓	✓
	Ripple					50PLE			✓
CONTROL INTERFACE	 DA	 DMX	 CSB						
INPUT	 24V								





NEBULA 3 WALL MOUNT

IP 66 IK08

DIMENSIONS (MM)




(DOWN)



(UP DOWN)

NEBULA 3 WALL MOUNT 66 IK08



SPECIFICATIONS

FIXTURE	
Family Type	NEBULA
Fixture Colours	Matt Grey (RAL7001), matt black (RAL9011), brushed bronze, brushed brass, brushed copper
Materials	Aluminium, Marine Grade Coating, Sealed Hard Anodising
Accessories	Shadow enhancer
Ingress Protection	IP66, IK08
DC Input Cable	Supplied with 1m cable. Custom length available upon request

Lifetime	100,000 hours (80% lumen maintenance at Ta = 25°C), B10
Light Themes	Cool Graphite, Warm Graphite, Golden, Silver, Ivory, Aqua, Sky Blue
Control Interface	DALI (NFC Copy & Paste), DMX, CASAMBI
Mains Voltage	24V DC constant voltage
Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability Mark	F
Safety Class	Class 3
Standards	IEC 62031
Regulatory Markings	CE, RoHS

LED MODULE & DRIVER	
Family Type	35, 50 series LED module and engines
Typical Operating Voltage	24V
Typical Operating Current	330mA - 495mA
System / Input Power	8W, 12W
Beam Angles	Dapple 20°, 35°, 60° / Ripple 55°

FIXTURE ORDERING MATRIX CHART

Type	Fixture				Accessories						
	Ingress Protection		Shape	Colour	Cable Length	Type	Accessory	Fixture Size			
NEBULA-3WM-B	IP66	IP66	D Down	GR	Matt Grey	1M	MP.ACC	SHA-D1 Shadow D1	-3		
				MB	Matt Black					3M	3000mm
				BBZ	Brushed Bronze					5M	5000mm
				BBR	Brushed Brass						
				BCP	Brushed Copper						
				UD	Up/Down						

example: NEBULA-3WM-B.IP66.D.MB.1M

example: MP.ACC.SHA-D1-3

Note: Custom RAL colour options available.

LED MODULE & DRIVER ORDERING MATRIX CHART

Input Power	LED Module			Control			
	Beam Angle		Light Theme	Interface			
ELR50PLE-BM.12	12W	20	20°	D4	Dapple - 4 Modes	DA	DALI
ELR50PLE-BM.8	8W	35	35°			DMX	DMX
		60	60°			CSB	Casambi

example: ELR50PLE-BM.8.35.D4.DA

Input Power	LED Module			Control			
	Beam Angle		Light Theme	Interface			
ELR50PLE-BM.12	12W	55	55°	R1-IV	Ripple - Ivory	DA	DALI
ELR50PLE-BM.8	8W			R1-AQ	Ripple - Aqua	DMX	DMX
				R1-GD	Ripple - Golden	CSB	Casambi
				R1-SB	Ripple - Sky Blue		

example: ELR50PLE-BM.8.55.R1-AQ.DA